



Your Water. Perfected.™

Let us

Perfect

your water and

Maximize


your peace of mind.

ERRC 3502

ECOWATER 3500 SERIES WATER CONDITIONING SYSTEM

The Latest Technology for Water Treatment

- 1 HydroLink® and HydroLinkPlus® Remote Monitor**
Patented two-way remote monitoring or Wi-Fi enabled technology and smartphone app.
- 2 Patented Electronics Digital Demand Module**
Sophisticated, yet easy-to-use electronics capture historical usage patterns to predict future needs for precise regenerations.
- 3 Multi-Wrap Fiberglass Reinforced Resin Tank**
Durable tank liner will not deteriorate, rust, or corrode.
- 4 Full One-Inch Riser**
One-inch diameter for increased flow rates, which ensures that household demand is adequately met.
- 5 Catalytic Coconut-Shell Carbon with 10 Year Warranty**
Filters the water throughout the home without compromising water flow. Reduces chloramines, removes chlorine taste and odor, extends resin life and eliminates the need for a separate carbon filter and filter changes.
- 6 Patented Stratified Resin Bed**
Layered mix of fine and standard size resin provides superior filtration and iron removal without sacrificing flow rate capability.
- 7 Positive-Action Brine Valve**
Snap-together construction eliminates use of solvents that may contaminate water. Positive action helps prevent overfilling.
- 8 Self-Cleaning Distributors**
Distributors exhibit excellent flow rates and are cleaned automatically by counter-current water pressure.
- 9 Washed Quartz Underbedding**
Helps provide a cleaner, more thorough regeneration of the resin.




Designed, Engineered &
Assembled in the U.S.A.

ecowater.ca

ERRC 3502

ECOWATER 3500 SERIES WATER CONDITIONING SYSTEM

DIMENSIONS



	ERRC 3502 R50
Nominal Resin Tank Size	12" Diam. x 54"
A	57.1"
B	62.2"

SPECIFICATIONS

ERRC 3502R50

Efficiency (gr./lb. @ min. lb. salt dose)	4,800 @ 4.5
Hardness Capacity (gr. @ max. lb. salt dose)	50,000 @ 17.4
Intermittent Flow Rate (gpm @ psi) ¹	15 @ 15
Intermittent Flow Rate (gpm @ psi) ¹	22 @ 30
Stratified Resin Bed (lbs.)	79.56
Quartz Gravel Base (lbs.)	10
Maximum Water Hardness (grains per gallon)	95
Chloramine Removal	<70% ²
Maximum Chlorine (ppm)	4
Approximate Water Used Each Regeneration (gal.) ³	95
Salt Storage Capacity (lbs.)	300
Supply Water Pressure Limits (psi) ⁴	20 – 125
Supply Water Temperature Limits (°F)	40 – 100
Ambient Temperature Range (°F)	35 – 150
Plumbing Connection Provided (inches)	1

Electrical Requirement, 120V, 50/60Hz, (28V DC, 350 mA, power supply included)

¹Intermittent flow rate does not represent the maximum service flow rate used for determining the conditioner's rated capacity and efficiency. Continuous operation at flow rates greater than the certified flow rate may affect capacity and efficiency performance. The validity of these flow rates is verified by NSF. ²<70% removal of chloramines for a minimum of 34,000 gallons @ 10 gpm. Typical residential chloramine level is < 1 ppm. ³When operated at 35 psi water pressure. ⁴Maximum pressure for Canadian use is 7.0 Kg/cm².



Your Water. Perfected.™



EcoWater Systems LLC
P.O. Box 64420
St. Paul, MN 55164-0420



EcoWater Canada Ltd.
5240 Bradco Blvd.
Mississauga, Ontario
Canada L4W 1G7



**EcoWater Systems
Europe N.V.**
Geelseweg 56 2250 Olen
Belgium



Kunshan EcoWater Systems Co. Ltd.
483 San Xiang Rd.
Kunshan, Jiangsu Province, PRC 215335